

Technical specification

Wool Classics: Riffle

Construction	Through back cut and loop Woven Wilton
Yarn content	100% wool
Pitch	31.6/dcm
Total pile height	Loop +/- 5.25mm Cut +/- 4.80mm
Total carpet thickness	+/- 7.5mm
Total pile weight	+/- 1425gms/m ²
Total carpet weight	+/- 2650gms/m ²
Backing fibres	Jute and polycotton
Back coat	Latex
Production width	+/- 3.66m
TOG rating	1.42 (Tested to BS4745: 2005/ISO 5085-1: 1989)
Flammability	BS4790: Pass
Suitability	Heavy domestic use – including stairs Medium contract – not suitable for stairs or castor chairs

Colour selection

Due to variations in bulk dyeing, it is not possible to obtain an exact colour match between different product batches. For this reason, all samples are a guide to colour and may not be an exact match to the available batch. Where a specific colour match is required, we recommend a stock cutting from the current batch is requested. It should be taken into consideration when selecting colours that darker shades camouflage the effects of soiling more than lighter shades. This is especially relevant in heavy use locations in both contract and residential situations.

Surface and visual effects

Certain variances, including linear effects and striations, in the pile surface texture are inherent in all quality wool carpets. To an overwhelming degree, these slight irregularities are due to the fact that wool is a natural material and as such must be allowed a greater tolerance than synthetic yarn. In patterns where there is a greater difference between the background and top shades, certain light sources may give rise to effects, which are strictly optical and not manufacturing defects. Pile movement during use may temporarily distort the linear pattern of this product.

Pile crush/tracking

Through use and in time all carpets will flatten to a certain degree. This is most noticeable in areas of concentrated use. We cannot accept responsibility for complaints caused by these effects, which are not manufacturing defects.

Installation

This is a specialist product and should only be installed by professional carpet fitters. We recommend the installer is provided with a sample of the selected carpet, to ensure they are familiar with the product type and it's suitability for the location and the proposed installation method. Specific consideration must be given when planning the use of this carpet on stairs. All aspects of sub-floor preparation and installation should be in accordance with the recommendations of BS5325/2001/ As with all carpets of this construction we are unable to guarantee an exact width-to-width pattern match. Additional technical information is available upon request.

Area rugs

This collection can be supplied, made to specific dimensions, as finished rugs or runners, bound with either Leather or Linen tapes or bordered in carpet using a contrasting colour from this range. Further details are available on request.

Cleaning and maintenance

A guide, giving handy hints on regular and programmed maintenance, is available free of charge on request.

Tolerances

All specifications are subject to normal manufacturing tolerances. The company reserves the right to modify carpet specifications without notice, where performance is not affected.

All information provided above and technical advice, whether verbal, written or by way of trial samples is for guidance only and is submitted in good faith, but without warranty, since the skill of installation and site conditions are beyond our control. The end user should be provided with a copy of the above.



Head Office

Wool Classics 19 Victoria Industrial Estate Victoria Road London W3 6UU

T: +44 (0) 20 8961 7721 (General)
+44 (0) 20 7349 0090 (Sales)

F: +44 (0) 20 7349 0035

sales@woolclassics.com
samples@woolclassics.com

www.woolclassics.com