

Technical specification

Wool Classics: Twyne

Construction	Tufted
Pile type	Hi-Lo loop pile
Yarn content	100% pure new wool (2 ply).
Rows	30/dcm
Total pile height	High loop +/- 7.0 mm Low loop +/- 4.5mm
Total carpet thickness	+/- 9.0mm
Total pile weight	+/- 1430g/m ² 42oz/yd ² +/- 5%
Backing fibres	Jute
Production width	+/- 3.66m (12' broadloom)
TOG rating	1.62
Flammability	BS4790: Pass
Suitability	Residential extra heavy duty (including stairs) *Contract light to medium duty (including stairs) *Contract suitability rating is for guideline purposes only – all contract installations should be assessed individually. Not recommended for use with castor chairs.

Colour selection

Due to variations in bulk dyeing, the colour in the finished carpet may vary slightly from those of the sample. Where a particular colour match is required, a stock cutting is available on request. It should be taken into consideration when selecting colours that darker shades camouflage soiling more than lighter shades. This is especially relevant in heavy use locations in both domestic or contract installations.

Surface and visual effects

Certain variances, including linear effects and striations, in the surface texture are inherent in all quality wool carpets. To an overwhelming degree, these slight irregularities are due to the fact that wool is a natural material and as such must be allowed a greater tolerance than synthetic yarn. In patterns where there is a greater difference between the background and top shades, certain light sources may give rise to effects, which are strictly optical and not manufacturing defects.

Shift lines

Construction of this carpet may involve shift lines occurring accruing across the width of the carpet. Certain light sources shining across the carpet may accentuate these lines in the form of shadowing. This effect is not a manufacturing fault and will not affect the carpets wear or durability.

Colour phasing

Colour phasing is a phenomenon inherent with a product of this type. It may appear as random colour banding and is due to the configuration of contrasting colours required to produce the Sisal effect. It is not a manufacturing fault and will not affect the performance characteristics of the carpet.

Installation

All aspects of sub-floor preparation and floor covering installation should be in accordance with the recommendations of BS5325, "The Installation of Textile Floor coverings". Your installer should be provided with a sample of the carpet to ensure they are familiar with the product type selected and understand the special techniques required when fitting a carpet of loop pile Wilton construction.

Tolerances

All specifications are subject to normal manufacturing tolerances. The company reserves the right to modify carpet specifications without notice, where performance is not affected.

All information provided above and technical advice, whether verbal, written or by way of trial samples is for guidance only and is submitted in good faith, but without warranty, since the skill of installation and site conditions are beyond control. The end user should be provided with a copy of the above.



Head Office

Wool Classics 19 Victoria Industrial Estate Victoria Road London W3 6UU

T: +44 (0) 20 8961 7721 (General)
+44 (0) 20 7349 0090 (Sales)

F: +44 (0) 20 7349 0035

sales@woolclassics.com
samples@woolclassics.com

www.woolclassics.com